

Liefhebber Forklifts.

Product List (Main Part)

No1. 4-Wheel Counterbalanced Electric Forklift

(Big Wheel Front Wheel 22X7-12 _{5.00} Rear Wheel 5.00-8 _{3.00})

Model		CPD1030	CPD1530	CPD2030	CPD3030
Parameter					
Load Capacity (Kg)		1000	1500	2000	3000
Lift Height (m)		3000	3000	3000	3000
Load Center (mm)		500	500	500	500
Fork Length (mm)		1070	1070	1070	1070
Lowest height (mm)		120	120	120	120
Manipulation Way		Steering Wheel	Steering Wheel	Steering Wheel	Steering Wheel
Tyres		Solid Wheel	Solid Wheel	Solid Wheel	Solid Wheel
Dimension of Driving Wheel		510mm	510mm	560mm	650mm
Speed at Full Load km/h		15	15	15	15
Lifting Speed at full Load mm/sec		200	200	200	200
Speed Control Way		Stepless Speed Regulation	Stepless Speed Regulation	Stepless Speed Regulation	Stepless Speed Regulation
Door Frame Tilt Angle °		3~6	3~6	3~6	3~6
Gradient at full Load °		15	15	15	15
Battery V/Ah		48/240	48/270	48/270	48/420
Working Time (for reference) (h)		3	3	3.5	6
Driving Motor (kw)		4	4.2	5	8
Lifting Motor (kw)		3	3	5.5	5.5

The Min. Turning Inner Radius (mm)	2000	2000	2100	2150
L X W X H Dimension (mm)	3380*1050*2100	3380*1050*2100	3450*1100*2100	3600*1160*2120
weight (kg)	2200	2400	2800	3800
lifting Height at each weight (mm)	1600/2000/2500/3000/3500			
Height of Door Frame (mm)	2080/1600/1850/2080/2350			

Product Picture Show (Big 4-Wheel)



No.2 4-Wheel Counterbalanced Electric Forklift (Small Wheel Front&Rear 4.00-8_{3.00})

Model		CPD1030	CPD1530
Load	Capacity	1000	1500
Lift Height (m)		3000	3000
Load	Center	500	500

Fork Length (mm)	1070	1070
Lowest height (mm)	60	60
Manipulation Way	Steering Wheel	Steering Wheel
Tyres	Solid Wheel	Solid Wheel
Speed at Full Load km/h	15	15
Lifting Speed at full Load mm/sec	200	200
Speed Control Way	Stepless Speed Regulation	Stepless Speed Regulation
Door Frame Tilt Angle °	4~6	4~6
Gradient at full Load °	8	8
Battery V/Ah	48/140	48/140
Working Time (for reference) (h)	4~6	4~6
Driving Motor (kw)	2/3	2/3
Lifting Motor (kw)	3	3
The Min. Turning Inner Radius (mm)	1700	1750
L X W X H Dimension (mm)	2770*1030*2100	2870*1030*2100
weight (kg)	1800	2100

Product Picture Show (Small 4-Wheel)



1.5 Ton 3M



1.5 Ton 3M



1 Ton 3M

No.3 3-Wheel Counterbalanced Electric Forklift

Model Parameter	CPD1030	CPD1530	CPD2030
Load Capacity (Kg)	1000	1500	2000
Lift Height (m)	3000	3000	3000
Load Center (mm)	500	500	500
Fork Length (mm)	1070	1070	1070
Lowest height (mm)	55	55	55
Manipulation Way	Steering Wheel	Steering Wheel	Steering Wheel

Tyres	Solid Tyre	Solid Tyre	Solid Tyre
Dimension of Driving Wheel	350*100	350*100	250*80
Speed at Full Load km/h	8	8	5
Lifting Speed at full Load mm/sec	80	80	80
Speed Control Way	Stepless Speed Regulation	Stepless Speed Regulation	Stepless Speed Regulation
Door Frame Tilt Angle °	3~6	3~6	3~6
Gradient at full Load °	3~5	3~5	3~5
Battery V/Ah	24/120	24/120	24/240
Working Time (for reference) (h)	4~6	4~6	3~5
Driving Motor (kw)	1.5	1.5	1.5
Lifting Motor (kw)	3	3	3
The Min. Turning Inner Radius (mm)	1750	1800	1800
L X W X H Dimension (mm)	2970*1050*2100	3070*1050*2100	3070*1050*2100
weight (kg)	1600	1700	1800

Product Picture Show (3-Wheel Electric Forklift)



No.4 Full Electric Stacker

Model	CDD1030	CDD1530	CDD2030
Parameter			
Load Capacity (Kg)	1000	1500	2000
Lift Height (m)	3000	3000	3000
Load Center (mm)	500	500	500
Fork Length (mm)	1070	1070	1070
Lowest height (mm)	25	25	25
Manipulation Way	Handle	Handle	Handle
Tyres	Nylon/PU	Nylon/PU	Nylon/PU
Dimension of Driving Wheel	250*80	250*80	250*80
Speed at Full Load km/h	5	5	5
Lifting Speed at full Load mm/sec	90	85	80
Speed Control Way	Stepless Speed Regulator	Stepless Speed Regulator	Stepless Speed Regulator
Door Frame Tilt Angle °	/	/	/
Gradient at full Load °	10	8	8
Battery V/Ah	24/180	24/180	24/180
Working Time (for reference) (h)	8	7	7
Driving Motor (kw)	1.2	1.2	1.5
Lifting Motor (kw)	2.2	2.2	3
The Min. Turning Inner Radius (mm)	1250	1250	1250
L X W X H Dimension (mm)	2000*860*2080	2000*860*2080	2000*860*2080

weight (kg)	680	700	750
lifting Height at each weight (mm)	1600/2000/2500/3000/3500		
Height of Door Frame (mm)	2080/1600/1850/2080/2350		

Product Picture Show (Full Electric Stacker)



No.5 Walkie Electric Forklift

Model	CDW1530
Load Capacity	1.5T
Lift Height	3000mm
Fork length	1070mm
The Stacker Length	1770mm
Height	2090mm
Width	850mm
Axle Distance	1250mm
Outer width between fork	680mm
Inner width between fork	305mm
The min. turning radius	1390mm
Driving speed at full load	3.5km/h
Lift speed at full load	135mm/s
Gradient at full load	5°
Type of driving motor	DC motor
Driving motor power	0.75kw
Type of lift motor	DC motor
Lift motor power	2.2kw
Battery	24V/80A

Product Picture Show (Walkie Electric Forklift)

